Wide micro spike spot

Technical specification / SPIKEW

Contents

Select a section or page number to jump to it. Use Contents in the footer to return.

01 Product overview 2

02 Light & electrical 3

03 Mechanical & construction 3

04 Service & circularity 3

05 Ordering 3

Generated from current saved product details, specification notes and published FAQs. Downloaded copies are dated snapshots. Regenerate after changes. Unanswered fields are omitted. Check suitability for your project before installation.

01 Product overview

Wide micro spike spot

Product code	SPIKEW
Product reference	23
Rated power (standard LED)	3.6 W
Ingress protection	IP68
Standard cable length	2.00 m
Standard weight	280 g
Warranty period	10 years

Product record updated: 2026-09-19 01:42:34

Specification notes revision: 0

02 Light & electrical

Available LED options (colour / power)	2700K / 1.6W 2700K / 2.6W 2700K / 3.6W 2200K / 1.6W

03 Mechanical & construction

Body material by finish	Black powder coat: CNC machined 6082-T6 aluminium Green powder coat: CNC machined 6082-T6 aluminium CorTen Powder coat: CNC machined 6082-T6 aluminium CUSTOM RAL: CNC machined 6082-T6 aluminium Terra brown (formerly Bronze (RAL 8040)): CNC machined 6082-T6 aluminium
Available finishes	Black powder coat; Green powder coat; CorTen Powder coat; CUSTOM RAL; Terra brown (formerly Bronze (RAL 8040))

04 Service & circularity

TM66 assessment score	2.6

05 Ordering

Available options	Glare guard (Micro); 100mm longer rod; 200mm longer rod; 250mm longer rod; 300mm longer rod; Upgrade CRI to 95 - Not applicable to Amber and not available on 3.6W